

EASY ROTO HVR + STAFF + TRIPOD PACK



Product description:

PACK comprises:

- EASY ROTO HVR ROTARY LASER
- TS5 500 CM STAFF
- GEO 167 CM TRIPOD

EASY ROTO HVR ROTARY LASER features

- Red beam and upper and lower plumb points.
- Automatic horizontal and vertical levelling.
- Manual mode option for creating inclined planes at any angle.
- Manual dual slope mode for creating inclined planes in planes X and Y up to $\pm 10\%$.
- Easy to adjust scan zone (0° , 10° , 45° , 90° , 180°) and rotation speed (0, 120, 300, 600 rpm).
- Reverse scan direction.
- Tilt mode: signals that the laser has been knocked or has moved from its starting position. Safety mode is then activated and rotation stops.
- Option to use laser keypad directly or remotely via your smartphone in Bluetooth ("ROTO Remote" application free to download from the App Store or Google Play).
- $5/8"$ thread for use with a tripod.

- Digital receiver with dual front/rear display.

Comes with

Laser mount, receiver, receiver mount, magnetic mount, glasses, storage case, Li-ion battery, battery charger, battery, user manual.

TS5 500 CM STAFF features

- Robust aluminium telescopic levelling staff.
- Minimum height 125 cm.
- Maximum height 500 cm.
- Continuous cm-E graduation on the front.
- Millimetre scale graduation on the rear.

GEO 167 CM TRIPOD features

- Aluminium tripod with head, compatible with industrial safety goggles, theodolites and rotary lasers.
- Minimum height 101 cm.
- Maximum height 167 cm.
- 5/8" thread
- Quick-release clamp on each foot.
- Feet equipped with spikes for outdoor work.
- Integrated transport strap.

Product features:

| | |
|---------------------------------|---|
| Laser Colour Feature : | Red |
| Range with Receiver Feature : | 400 m |
| Accuracy Feature : | ± 0,15 mm/m |
| Automatic leveling range : | ± 5° |
| Tilt range X and Y : | ± 10 % |
| Laser Feature : | 630-685 nm, inf.1 mW, class II |
| Autonomy Feature : | 35 h |
| Ingress Protection Feature : | IP55 |
| Bluetooth Feature : | Yes |
| Power Supply Feature : | 7,4 V 4000 mAh Li-ion battery and 1 x 9 V 6LR61/6F22 battery for receiver |
| Operating Temperature Feature : | -20 °C... +50 °C |
| Storage Temperature Feature : | -20 °C... +50 °C |
| Dimensions Feature : | 150 x 128 x 161 mm |
| Weight Feature : | 1500 g |
| Ref. Feature : | C72113 |
| EAN Code Feature : | 4620752698377 |

