EASY ROTO HVR + STAFF + TRIPOD PACK

Product description:

PACK comprises:
- EASY ROTO HVR ROTARY LASER
- TS5 500 CM STAFF
- GEO 167 CM TRIPOD

EASY ROTO HVR ROTARY LASER features

- Red beam and upper and lower plumb points.
- Automatic horizontal and vertical levelling.
- Manual mode option for creating inclined planes at any angle.
- Manual dual slope mode for creating inclined planes in planes X and Y up to ± 10%.
- Easy to adjust scan zone (0°, 10°, 45°, 90°, 180°) and rotation speed (0, 120, 300, 600 rpm).
- Reverse scan direction.
- Tilt mode: signals that the laser has been knocked or has moved from its starting position. Safety mode is then activated and rotation stops.
- Option to use laser keypad directly or remotely via you smartphone in Bluetooth ("ROTO Remote" application free to download from the App Store or Google Play).
- 5/8" thread for use with a tripod.

- Digital receiver with dual front/rear display.

Comes with

Laser mount, receiver, receiver mount, magnetic mount, glasses, storage case, Li-ion battery, battery charger, battery, user manual.

TS5 500 CM STAFF features

- Robust aluminium telescopic levelling staff.
- Minimum height 125 cm.
- Maximum height 500 cm.
- Continuous cm-E graduation on the front.
- Millimetre scale graduation on the rear.

GEO 167 CM TRIPOD features

- Aluminium tripod with head, compatible with industrial safety goggles, theodolites and rotary lasers.
- Minimum height 101 cm.
- Maximum height 167 cm.
- 5/8" thread
- Quick-release clamp on each foot.
- Feet equipped with spikes for outdoor work.
- Integrated transport strap.

Product features:

Laser Colour :	**Red**
Range with Receiver :	**400 m**
Accuracy :	**± 0,15 mm/m**
Automatic leveling range :	**± 5°**
Tilt range X and Y :	**± 10 %**
Laser :	**630-685 nm, inf.1 mW, class II**
Autonomy :	**35 h**
Ingress Protection :	**IP55**
Bluetooth Feature :	**Yes**
Power Supply :	**7,4 V 4000 mAh Li-ion battery and 1 x 9 V 6LR61/6F22 battery for receiver**
Operating Temperature :	**-20 °C… +50 °C**
Storage Temperature :	**-20 °C… +50 °C**
Dimensions :	**150 x 128 x 161 mm**
Weight :	**1500 g**
Ref. :	**C72113**
EAN Code :	**4620752698377**