

# EASY ROTO HVR + STAFF + TRIPOD PACK



---

## Product description:

### PACK comprises:

- EASY ROTO HVR ROTARY LASER
- TS5 500 CM STAFF
- GEO 167 CM TRIPOD

### EASY ROTO HVR ROTARY LASER features

- Red beam and upper and lower plumb points.
- Automatic horizontal and vertical levelling.
- Manual mode option for creating inclined planes at any angle.
- Manual dual slope mode for creating inclined planes in planes X and Y up to  $\pm 10\%$ .
- Easy to adjust scan zone ( $0^\circ$ ,  $10^\circ$ ,  $45^\circ$ ,  $90^\circ$ ,  $180^\circ$ ) and rotation speed (0, 120, 300, 600 rpm).
- Reverse scan direction.
- Tilt mode: signals that the laser has been knocked or has moved from its starting position. Safety mode is then activated and rotation stops.
- Option to use laser keypad directly or remotely via your smartphone in Bluetooth ("ROTO Remote" application free to download from the App Store or Google Play).
- $5/8"$  thread for use with a tripod.

- Digital receiver with dual front/rear display.

## Comes with

Laser mount, receiver, receiver mount, magnetic mount, glasses, storage case, Li-ion battery, battery charger, battery, user manual.

## TS5 500 CM STAFF features

- Robust aluminium telescopic levelling staff.
- Minimum height 125 cm.
- Maximum height 500 cm.
- Continuous cm-E graduation on the front.
- Millimetre scale graduation on the rear.

## GEO 167 CM TRIPOD features

- Aluminium tripod with head, compatible with industrial safety goggles, theodolites and rotary lasers.
- Minimum height 101 cm.
- Maximum height 167 cm.
- 5/8" thread
- Quick-release clamp on each foot.
- Feet equipped with spikes for outdoor work.
- Integrated transport strap.

---

## Product features:

|                            |   |
|----------------------------|---|
| Laser Colour :             | Red   |
| Range with Receiver :      | 400 m   |
| Accuracy :                 | ± 0,15 mm/m   |
| Automatic leveling range : | ± 5°  |
| Tilt range X and Y :       | ± 10 %  |
| Laser :                    | 630-685 nm, inf.1 mW, class II  |
| Autonomy :                 | 35 h  |
| Ingress Protection :       | IP55  |
| Bluetooth Feature :        | Yes   |
| Power Supply :             | 7,4 V 4000 mAh Li-ion battery and 1 x 9 V 6LR61/6F22 battery for receiver |
| Operating Temperature :    | -20 °C... +50 °C  |
| Storage Temperature :      | -20 °C... +50 °C  |
| Dimensions :               | 150 x 128 x 161 mm  |
| Weight :                   | 1500 g  |
| Ref. :                     | C72113  |
| EAN Code :                 | 4620752698377   |

