

FLIESEN 4D



Product description:

Green laser level

Features

- 2 horizontal 360° green line and 2 vertical 360° green lines. Lines operate independently.
- 2 operating modes: automatic and manual.
- Can be used with a receiver (optional).
- 1/4" thread and 5/8" thread for use with a tripod.
- Can be mounted by lifting platform, wall mount and clamp mount.

Delivered with

aluminium lifting platform, Wall Mount Pro wall mount, clamp mount, magnetic target, storage case, 2 Li-ion batteries, charging cable, user manual.

Product features:

New:	Yes
Laser Colour Feature :	Green
Range:	30 m







Range with Receiver Feature :	60 m
Accuracy Feature :	± 0,3 mm/m
Automatic leveling range :	± 3°
Laser Feature :	515 nm, inf.1 mW, class II
Autonomy Feature :	5 h
Ingress Protection Feature :	IP54
Distance between the lower horizontal line and the ground:	18 mm
Distance between the lower horizontal line and the ground with the platform:	adjustable from 30 to 90 mm
Power Supply Feature :	3,7 V 4000 mAh Li-ion battery
Operating Temperature Feature :	-10 °C +40 °C
Storage Temperature Feature :	-15 °C +50 °C
Dimensions Feature :	147 x 91 x 147 mm
Weight Feature :	878 g
Ref. Feature :	C1002002
EAN Code Feature :	4620752699046



