

XLINER COMBO 360G KIT



Product description:

Green laser level + wall mount

Features

- 1 vertical green line and 1 horizontal 360° green line + plumb points.
- Lines operate independently.
- 2 operating modes: automatic and manual.
- Can be used with a receiver (optional).
- 1/4" thread and 5/8" thread for use with a tripod.
- 2 mounting options: wall mount and screw to wall using slot on rear of casing.

- Bluetooth for remote control via your smartphone ("XLINER Remote" application free to download from the App Store or Google Play).

Comes with

Wall Mount Pro wall mount, clamp mount, magnetic target, storage case, batteries, user manual.

Product features:







Range :40 mRange with Receiver Feature :80 mAccuracy Feature :± 0,2 mm/mAutomatic leveling range :± 3,5°Laser Feature :520 nm, inf.1 mW, class IIIngress Protection Feature :IP54Bluetooth Feature :YesPower Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412EAN Code Feature :4620753698346	Laser Colour Feature :	Green
Accuracy Feature :± 0,2 mm/mAutomatic leveling range :± 3,5°Laser Feature :520 nm, inf.1 mW, class IIIngress Protection Feature :IP54Bluetooth Feature :YesPower Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Range :	40 m
Automatic leveling range :± 3,5°Laser Feature :520 nm, inf.1 mW, class IIIngress Protection Feature :IP54Bluetooth Feature :YesPower Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Range with Receiver Feature :	80 m
Laser Feature :520 nm, inf.1 mW, class IIIngress Protection Feature :IP54Bluetooth Feature :YesPower Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Accuracy Feature :	± 0,2 mm/m
Ingress Protection Feature :IP54Bluetooth Feature :YesPower Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Automatic leveling range :	± 3,5°
Bluetooth Feature :YesPower Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Laser Feature :	520 nm, inf.1 mW, class II
Power Supply Feature :4 x 1,5 V LR6/AA batteriesOperating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Ingress Protection Feature :	IP54
Operating Temperature Feature :-10 °C +50 °CStorage Temperature Feature :-20 °C +70 °CDimensions Feature :320 x 320 x 150 mmWeight Feature :2500 gRef. Feature :C12412	Bluetooth Feature :	Yes
Storage Temperature Feature : -20 °C +70 °C Dimensions Feature : 320 x 320 x 150 mm Weight Feature : 2500 g Ref. Feature : C12412	Power Supply Feature :	4 x 1,5 V LR6/AA batteries
Dimensions Feature : 320 x 320 x 150 mm Weight Feature : 2500 g Ref. Feature : C12412	Operating Temperature Feature :	-10 °C +50 °C
Weight Feature : 2500 g Ref. Feature : C12412	Storage Temperature Feature :	-20 °C +70 °C
Ref. Feature : C12412	Dimensions Feature :	320 x 320 x 150 mm
	Weight Feature :	2500 g
EAN Code Feature : /6207526083/6	Ref. Feature :	C12412
	EAN Code Feature :	4620752698346
Warranty Feature : 2+1 years	Warranty Feature :	2+1 years

