

ROTO HVR



Product description:

Red rotary laser

Features

- Red beam and upper and lower plumb point.
- Automatic horizontal and vertical levelling.
- Manual mode option for creating inclined planes at any angle.
- Manual dual slope mode for creating inclined planes in planes X and Y up to $\pm 10\%$.
- Easy to adjust scan zone (0° , 10° , 45° , 90° , 180°) and rotation speed (0, 60, 120, 300, 600 rpm).
- Reverse scan direction.
- Tilt mode: signals that the laser has been knocked or has moved from its starting position. Safety mode is then activated and rotation stops.
- 5/8" thread for use with a tripod.
- Digital receiver with dual front/rear display and millimeter scale.

Comes with

Receiver, receiver mount, remote control, magnetic target, glasses, storage case, Ni-MH battery, battery charger, adaptor for 4 LR14/AM2 batteries, batteries, user manual.

Product features:

Laser Colour Feature :

Red

Range with Receiver Feature :	600 m
Accuracy Feature :	± 0,09 mm/m
Automatic leveling range :	± 5°
Tilt range X and Y :	± 10 %
Laser Feature :	635 nm, inf.1 mW, class II
Autonomy Feature :	20 h
Ingress Protection Feature :	IP67
Power Supply Feature :	4 x 1,2 V 4000 mAh SC Ni-MH or 4 x 1,5 V LR14/C/AM2 batteries, 2 x 1,5 V LR03/AAA batteries for remote control and 1 x 9 V 6LR61/6F22 battery for receiver
Operating Temperature Feature :	-20 °C... +50 °C
Storage Temperature Feature :	-20 °C... +60 °C
Dimensions Feature :	206 x 206 x 211 mm
Weight Feature :	2500 g
Ref. Feature :	C72000
EAN Code Feature :	4620752696854
Warranty Feature :	2+1 years