

PAINT PRO - Coating thickness meter



Product description:

Coating thickness meter

Features

3 mode sensor: automatic, magnetic (ferrous metals) and vortex (non-ferrous metals).
Single or continuous measurement modes for taking measurements without removing the device from the surface, with dynamic screen display.
Direct maximum, minimum and average value readings display.
2 units of measurement: μm and mm, with automatic switchover based on the result.
Audio signal for measurements outside the selected range.
Memory for 320 readings (80 per group) and on-screen display.
USB interface for connection to PC and data analysis program.
Backlit LCD display.
Charge level indicator.

Comes with

2 metal plates (aluminium and iron), 0,05 mm/0,1 mm/0,25 mm/0,5 mm/1 mm thickness reference samples, strap, micro USB cable, CD-R, storage case, batteries, user manual.



Product features:

| | |
|---------------------------------|------------------------------|
| Accuracy Feature : | ± 3% |
| Ingress Protection Feature : | IP54 |
| Plage de mesure : | 0...1500 µm |
| Power Supply Feature : | 2 x 1,5 V LR03/AAA batteries |
| Operating Temperature Feature : | 0 °C... +45 °C |
| Storage Temperature Feature : | -10 °C... +50 °C |
| Dimensions Feature : | 112 x 51 x 28 mm |
| Weight Feature : | 80 g |
| Ref. Feature : | C37051 |
| EAN Code Feature : | 4620752694874 |
| Warranty Feature : | 2+1 years |

