PAINT PRO - Coating thickness meter

Product description:

Coating thickness meter

Features

3 mode sensor: automatic, magnetic (ferrous metals) and vortex (non-ferrous metals).
Single or continuous measurement modes for taking measurements without removing the device from the surface, with dynamic screen display.
Direct maximum, minimum and average value readings display.
2 units of measurement: ?m and mm, with automatic switchover based on the result.
Audio signal for measurements outside the selected range.
Memory for 320 readings (80 per group) and on-screen display.
USB interface for connection to PC and data analysis program.
Backlit LCD display.
Charge level indicator.

Comes with

2 metal plates (aluminium and iron), 0,05 mm/0,1 mm/0,25 mm/0,5 mm/1 mm thickness reference samples, strap, micro USB cable, CD-R, storage case, batteries, user manual.

Product features:

Accuracy Feature :	**± 3%**
Ingress Protection Feature :	**IP54**
Plage de mesure :	**0…1500 µm**
Power Supply Feature :	**2 x 1,5 V LR03/AAA batteries**
Operating Temperature Feature :	**0 °C… +45 °C**
Storage Temperature Feature :	**-10 °C… +50 °C**
Dimensions Feature :	**112 x 51 x 28 mm**
Weight Feature :	**80 g**
Ref. Feature :	**C37051**
EAN Code Feature :	**4620752694874**
Warranty Feature :	**2+1 years**

CONDTROL
une mesure de référence
POWERED.
EDMA
www.condtrol.fr